

Package ‘h3sdm’

May 29, 2026

Type Package

Title Species Distribution Modeling with H3 Grids

Version 0.1.4

Description Provides tools for species distribution modeling using H3 hexagonal grids (Uber Technologies Inc., 2022, <<https://h3geo.org>>). Facilitates retrieval of species occurrence records, generation of H3 grids, computation of landscape metrics, and preparation of spatial data for modern species distribution models workflows. Designed for biodiversity and landscape ecology research.

URL <https://github.com/ManuelSpinola/h3sdm>

BugReports <https://github.com/ManuelSpinola/h3sdm/issues>

License MIT + file LICENSE

Encoding UTF-8

Depends R (>= 4.1)

Config/Needs/website tidyverse/tidytemplate

Imports stats, sf, dplyr, purrr, tibble, rlang, terra, spatialsample, recipes, rsample, tune, workflows, yardstick, ecospat, DALEX, stacks

Suggests ggplot2, paisaje, knitr, rmarkdown, here, tidyr, themis, DALEXtra, ingredients, exactextractr, landscapemetrics, h3jsr, tidyterra, spocc, tidymodels, workflowsets, ranger, xgboost, ggbrick, parsnip, tidyverse, rbiodatacr, vip

VignetteBuilder knitr

LazyData true

Language en-US

Config/roxygen2/version 8.0.0

NeedsCompilation no

Author Manuel Spínola [aut, cre]

Maintainer Manuel Spínola <mspinola10@gmail.com>

Repository CRAN

Date/Publication 2026-05-29 20:50:02 UTC

Contents

bioclim_current	2
bioclim_future	3
cr_outline_c	4
h3sdm_aoa	4
h3sdm_calculate_it_metrics	6
h3sdm_classify	7
h3sdm_compare_models	8
h3sdm_count_from_records	9
h3sdm_data	11
h3sdm_eval_metrics	12
h3sdm_explain	13
h3sdm_extract_cat	14
h3sdm_extract_num	16
h3sdm_fit_model	17
h3sdm_fit_models	18
h3sdm_get_grid	20
h3sdm_get_records	21
h3sdm_get_records_by_hexagon	22
h3sdm_pa	24
h3sdm_pa_from_records	25
h3sdm_predict	27
h3sdm_predictors	28
h3sdm_recipe	29
h3sdm_recipe_gam	30
h3sdm_spatial_cv	31
h3sdm_stack_fit	32
h3sdm_workflow	33
h3sdm_workflows	34
h3sdm_workflow_gam	36
records	37
Index	39

bioclim_current	<i>Current bioclimatic raster</i>
-----------------	-----------------------------------

Description

A GeoTIFF with current bioclimatic variables for Costa Rica.

Format

GeoTIFF file, readable with `terra::rast()`.

Details

This file is stored in `inst/extdata/` and can be accessed with: `terra::rast(system.file("extdata", "bioclim_current.tif", package = "h3sdm"))`

Examples

```
library(terra)
bio <- terra::rast(system.file("extdata", "bioclim_current.tif", package = "h3sdm"))
```

bioclim_future	<i>Future bioclimatic raster</i>
----------------	----------------------------------

Description

A GeoTIFF with projected bioclimatic variables for Costa Rica.

Format

GeoTIFF file, readable with `terra::rast()`.

Details

This dataset corresponds to the climate projection:

- Model: INM-CM4-8
- Scenario: SSP1-2.6
- Period: 2021–2040

The file is stored in `inst/extdata/` and can be accessed with: `terra::rast(system.file("extdata", "bioclim_future.tif", package = "h3sdm"))`

Examples

```
library(terra)
bio <- terra::rast(system.file("extdata", "bioclim_future.tif", package = "h3sdm"))
```

cr_outline_c	<i>Costa Rica Continental Outline</i>
--------------	---------------------------------------

Description

A simplified outline of Costa Rica as an sf object.

Usage

```
cr_outline_c
```

Format

An sf object containing polygon geometry of Costa Rica.

Source

Adapted from publicly available geographic data.

Examples

```
library(sf)
plot(cr_outline_c)
```

h3sdm_aoa	<i>Area of Applicability (AOA) of spatial prediction models</i>
-----------	-----------------------------------------------------------------

Description

Estimates the Dissimilarity Index (DI) and the Area of Applicability (AOA) for new data given the training data and a fitted model. This function is designed to be applied directly to the output of [h3sdm_predict\(\)](#), so that both the predicted values and the AOA are available in a single sf object ready for mapping.

Usage

```
h3sdm_aoa(newdata, train, fit_object, cv = NULL, verbose = TRUE)
```

Arguments

newdata	An sf object, typically the direct output of h3sdm_predict() , containing the predictor variables and a prediction column.
train	An sf object, typically the output of h3sdm_data() , containing the training observations with the same predictor variables used in fit_object.
fit_object	The list returned by h3sdm_fit_model() , used to extract the model formula (predictor variable names) and variable importances when available.

cv	An rset object returned by <code>h3sdm_spatial_cv()</code> , used to extract cross-validation fold assignments. If NULL (default), Leave-One-Out (LOO) cross-validation is used.
verbose	Logical. Should progress messages be printed? Default TRUE.

Details

The algorithm follows Meyer & Pebesma (2021). Predictor variables are extracted automatically from the model formula inside `fit_object`. They are standardized using z-score scaling computed from `train`, then optionally weighted by variable importance. The mean nearest-neighbor distance among training points (`trainDist_avrgmean`) is used to normalize DI values. The AOA threshold is the maximum cross-validated training DI after removing outliers with Tukey's rule ($Q3 + 1.5 * IQR$). Locations with $DI \leq \text{threshold}$ are inside the AOA; locations above the threshold should be interpreted with caution.

Variable importance is extracted automatically for `ranger` and `xgboost` models via `vip::vi()`. For GAM models, or when importance cannot be extracted, all variables receive equal weight.

Value

The input `newdata sf` object with two additional columns:

DI Numeric. Dissimilarity Index for each observation. Values near 0 indicate high similarity to the training data; larger values indicate increasing dissimilarity.

AOA Integer. 1 = inside the AOA; 0 = outside the AOA.

References

Meyer, H., Pebesma, E. (2021): Predicting into unknown space? Estimating the area of applicability of spatial prediction models. *Methods in Ecology and Evolution* 12: 1620–1633. doi:[10.1111/2041-210X.13650](https://doi.org/10.1111/2041-210X.13650)

See Also

[h3sdm_predict\(\)](#), [h3sdm_fit_model\(\)](#), [h3sdm_spatial_cv\(\)](#), [h3sdm_data\(\)](#)

Examples

```
## Not run:
cv <- h3sdm_spatial_cv(dat, method = "block")
fit <- h3sdm_fit_model(workflow, cv)
pred <- h3sdm_predict(fit, new_data = h7)
result <- h3sdm_aoa(pred, train = dat, fit_object = fit, cv = cv)

## End(Not run)
```

`h3sdm_calculate_it_metrics`*Calculate Information Theory Landscape Metrics for Hexagonal Grid*

Description

Calculates 5 Information Theory (IT)-based landscape metrics (condent, ent, jointent, mutinf, relmutinf) for each hexagon in a given H3 hexagonal grid.

Usage

```
h3sdm_calculate_it_metrics(landscape_raster, sf_grid)
```

Arguments

`landscape_raster` A categorical `SpatRaster` containing land-cover data.

`sf_grid` An `sf` object containing the hexagonal grid with species or land-cover data.

Details

This function computes landscape metrics using the `landscapemetrics::sample_lsm()` workflow. The results are pivoted to a wide format for easy use.

Value

An `sf` object containing the input hex grid with new columns for each calculated metric.

References

Hesselbarth et al., 2019. `landscapemetrics`: an open-source R tool to calculate landscape metrics. *Ecography* 42: 1648–1657.

Nowosad & Stepinski, 2019. Information theory as a consistent framework for landscape patterns. [doi:10.1007/s1098001900830x](https://doi.org/10.1007/s1098001900830x)

Examples

```
library(sf)
library(terra)

# Create a categorical SpatRaster (land-cover map)
landscape_raster <- terra::rast(
  nrows = 30, ncols = 30,
  xmin = -85.0, xmax = -83.0,
  ymin = 9.0, ymax = 11.0,
  crs = "EPSG:4326"
)
terra::values(landscape_raster) <- sample(1:4, terra::ncell(landscape_raster),
```

```
replace = TRUE)
names(landscape_raster) <- "landcover"

# Create a simple hexagon grid as sf polygons
hex_grid <- sf::st_make_grid(
  sf::st_as_sfc(sf::st_bbox(c(
    xmin = -84.5, xmax = -83.5,
    ymin = 9.5, ymax = 10.5
  )), crs = sf::st_crs(4326))),
  n = c(3, 3),
  square = FALSE
)
sf_grid <- sf::st_sf(h3_address = paste0("hex_", seq_along(hex_grid)),
  geometry = hex_grid)

# Calculate Information Theory (IT) landscape metrics per hexagon
result_sf <- h3sdm_calculate_it_metrics(landscape_raster, sf_grid)
head(result_sf)
```

h3sdm_classify

Classify predictions based on an optimal threshold

Description

Converts continuous probability predictions into binary presence/absence based on a specified threshold.

Usage

```
h3sdm_classify(predictions_sf, threshold)
```

Arguments

`predictions_sf` An sf object containing a numeric column named prediction, typically produced by `h3sdm_predict()`.

`threshold` A numeric value representing the probability threshold (e.g., 0.45) above which predictions are classified as presence (1).

Details

This function is useful for converting continuous probability outputs into binary presence/absence data for mapping or model evaluation purposes.

Value

An sf object with the same geometry and all original columns, plus a new integer column `predicted_presence` with values 0 (absence) or 1 (presence).

Examples

```
## Not run:
library(sf)
library(dplyr)

# Crear un sf de ejemplo
df <- data.frame(
  id = 1:5,
  prediction = c(0.2, 0.6, 0.45, 0.8, 0.3),
  lon = c(-75, -74, -73, -72, -71),
  lat = c(10, 11, 12, 13, 14)
)

df_sf <- st_as_sf(df, coords = c("lon", "lat"), crs = 4326)

# Clasificar usando un umbral
classified_sf <- h3sdm_classify(df_sf, threshold = 0.5)

# Revisar resultados
print(classified_sf)

## End(Not run)
```

h3sdm_compare_models *Compare multiple H3SDM species distribution models*

Description

Computes and combines performance metrics for multiple species distribution models created with `h3sdm_fit_models()` or similar workflows. Metrics include standard yardstick metrics (ROC AUC, TSS, Boyce index, etc.). Returns a tibble summarizing model performance.

Usage

```
h3sdm_compare_models(h3sdm_results)
```

Arguments

`h3sdm_results` A list or workflow set containing fitted models with a metrics tibble. Typically, this object is the output of `h3sdm_fit_models()`.

Value

A tibble with one row per model per metric, containing:

- model** Model name
- .metric** Metric name (ROC AUC, TSS, Boyce, etc.)
- .estimator** Metric type (usually "binary")
- mean** Metric value

Examples

```
# Minimal reproducible example
example_metrics <- tibble::tibble(
  model = c("model1", "model2"),
  .metric = c("roc_auc", "tss_max"),
  .estimator = c("binary", "binary"),
  mean = c(0.85, 0.7)
)
example_results <- list(metrics = example_metrics)
h3sdm_compare_models(example_results)
```

h3sdm_count_from_records

Generate species richness or abundance count dataset from records

Description

Takes a user-provided dataset with presence records (from Excel, fieldwork, acoustic detections, camera traps, or any other source) and generates a hexagonal grid with counts (species richness, total detections, or individuals) ready for analysis with h3sdm. The input can be a `data.frame` with coordinate columns or an `sf` object. Coordinates are assumed to be in WGS84 (EPSG:4326).

Usage

```
h3sdm_count_from_records(
  records,
  aoi_sf,
  res = 7,
  expand_factor = 0.1,
  lon_col = "x",
  lat_col = "y",
  species_col = NULL,
  count_type = c("richness", "detections", "individuals"),
  presence_col = NULL,
  abundance_col = NULL,
  confidence_col = NULL,
  confidence_threshold = NULL,
  date_col = NULL,
  date_min = NULL,
  date_max = NULL
)
```

Arguments

`records` data.frame or sf object containing records.

aoi_sf	sf AOI (area of interest) polygon.
res	integer H3 resolution for the hexagonal grid. Default 7.
expand_factor	numeric Factor to expand AOI before creating hex grid. Default 0.1.
lon_col	character Name of the longitude column. Ignored if records is already an sf object. Default "x".
lat_col	character Name of the latitude column. Ignored if records is already an sf object. Default "y".
species_col	character Name of the column containing species names. Required when count_type = "richness".
count_type	character One of "richness" (number of unique species per hexagon), "detections" (total number of records per hexagon), or "individuals" (sum of a numeric abundance column per hexagon). Default "richness".
presence_col	character Optional. Name of the column indicating presence (1) or absence (0). If provided, only records with value == 1 are used.
abundance_col	character Required when count_type = "individuals". Name of the column with individual counts to sum per hexagon.
confidence_col	character Optional. Name of the column with detection confidence scores (numeric between 0 and 1). Useful for acoustic detection data (e.g. BirdNET output).
confidence_threshold	numeric Optional. Minimum confidence score to retain a record. Ignored if confidence_col is NULL.
date_col	character Optional. Name of the date column. The column must be of class Date. If your dates are stored as Excel numeric values, convert them first with as.Date(datos\$Fecha, origin = "1899-12-30").
date_min	character or Date Optional. Minimum date to retain records (inclusive). Format "YYYY-MM-DD".
date_max	character or Date Optional. Maximum date to retain records (inclusive). Format "YYYY-MM-DD".

Value

sf object with columns:

h3_address H3 index of the hexagon.

count Numeric count per hexagon (richness, detections, or individuals).

geometry MULTIPOLYGON of each hexagon.

Examples

```
data(cr_outline_c, package = "h3sdm")

my_records <- data.frame(
  x      = c(-84.1, -84.2, -83.9, -84.0, -84.1),
  y      = c(9.9, 10.1, 9.8, 9.95, 10.0),
```

```

Especie = c("Ara macao", "Ara macao", "Pharomachrus mocinno",
            "Tapirus bairdii", "Ara macao"),
Presencia = c(1, 1, 1, 1, 0)
)

richness_hex <- h3sdm_count_from_records(
  records      = my_records,
  aoi_sf       = cr_outline_c,
  res          = 7,
  lon_col      = "x",
  lat_col      = "y",
  species_col  = "Especie",
  count_type   = "richness",
  presence_col = "Presencia"
)

```

h3sdm_data

Combine species and environmental data for SDMs using H3 grids

Description

Combines species presence–absence data with environmental predictors. It also calculates centroid coordinates (x and y) for each hexagon grid cell.

Usage

```
h3sdm_data(pa_sf, predictors_sf)
```

Arguments

`pa_sf` An sf object from `h3sdm_pa()` containing species presence–absence data.
`predictors_sf` An sf object from `h3sdm_predictors()` containing environmental predictors.

Value

An sf object containing species presence–absence, environmental predictor variables, and centroid coordinates for each hexagon cell.

Examples

```

## Not run:
my_species_pa <- h3sdm_pa("Panthera onca", res = 6)
my_predictors <- h3sdm_predictors(my_species_pa)
combined_data <- h3sdm_data(my_species_pa, my_predictors)

## End(Not run)

```

h3sdm_eval_metrics *Evaluate performance metrics for a fitted H3SDM model*

Description

Computes a set of performance metrics for a single fitted species distribution model. Includes standard yardstick metrics such as ROC AUC, accuracy, sensitivity, specificity, F1-score, Kappa, as well as ecological metrics such as the True Skill Statistic (TSS) and Boyce index. This function is designed as a helper for evaluating models produced by `h3sdm_fit_model` or `h3sdm_fit_models`.

Usage

```
h3sdm_eval_metrics(
  fitted_model,
  presence_data = NULL,
  truth_col = "presence",
  pred_col = ".pred_1"
)
```

Arguments

<code>fitted_model</code>	A fitted model object, typically the output of <code>h3sdm_fit_model()</code> .
<code>presence_data</code>	Optional. An <code>sf</code> object or tibble containing presence locations used to compute the Boyce index. If not provided, the Boyce index will not be calculated.
<code>truth_col</code>	Character. Name of the column containing the true presence/absence values (default "presence").
<code>pred_col</code>	Character. Name of the column containing predicted probabilities (default ".pred_1").

Details

This function centralizes model evaluation for a single fitted H3SDM model, combining both general classification metrics and ecological indices. It is especially useful for systematically comparing model performance across species or modeling approaches.

Value

A tibble with one row per metric, containing:

.metric Metric name (e.g., "roc_auc", "tss", "boyce").

.estimator Estimator type (usually "binary").

mean Metric value.

std_err Standard error (NA for TSS and Boyce).

conf_low Lower bound of the 95% confidence interval (NA for TSS and Boyce).

conf_high Upper bound of the 95% confidence interval (NA for TSS and Boyce).

Examples

```
## Not run:
# Assuming 'fitted' is the result of h3sdm_fit_model()
metrics <- h3sdm_eval_metrics(
  fitted_model = fitted,
  presence_data = presence_sf,
  truth_col = "presence",
  pred_col = ".pred_1"
)
print(metrics)

## End(Not run)
```

h3sdm_explain

Create a DALEX explainer for h3sdm workflows

Description

Creates a DALEX explainer for a species distribution model fitted with `h3sdm_fit_model()`. Prepares response and predictor variables, ensuring that all columns used during model training (including `h3_address` and coordinates) are included. The explainer can be used for feature importance, model residuals, and other DALEX diagnostics.

Usage

```
h3sdm_explain(model, data, response = "presence", label = "h3sdm workflow")
```

Arguments

<code>model</code>	A fitted workflow returned by <code>h3sdm_fit_model()</code> .
<code>data</code>	A <code>data.frame</code> or <code>sf</code> object containing the original predictors and response variable. If an <code>sf</code> object, geometry is dropped automatically.
<code>response</code>	Character string specifying the name of the response column. Must be a binary factor or numeric vector (0/1). Defaults to "presence".
<code>label</code>	Character string specifying a label for the explainer. Defaults to "h3sdm workflow".

Value

An object of class `explainer` from the **DALEX** package, ready to be used with `feature_importance()`, `model_performance()`, `predict_parts()`, and other DALEX functions.

Examples

```

library(h3sdm)
library(DALEX)
library(parsnip)

dat <- data.frame(
  x1 = rnorm(20),
  x2 = rnorm(20),
  presence = factor(sample(0:1, 20, replace = TRUE))
)

model <- logistic_reg() |>
  fit(presence ~ x1 + x2, data = dat)

explainer <- h3sdm_explain(model, data = dat, response = "presence")
feature_importance(explainer)

```

h3sdm_extract_cat

Calculate Area Proportions for Categorical Raster Classes

Description

Extracts and calculates the **area proportion** of each land-use/land-cover (LULC) category found within each input polygon of the `sf_hex_grid`. This function is tailored for categorical rasters and ensures accurate, sub-pixel weighted statistics.

Usage

```
h3sdm_extract_cat(spat_raster_cat, sf_hex_grid, proportion = TRUE)
```

Arguments

<code>spat_raster_cat</code>	A single-layer <code>SpatRaster</code> object containing categorical values (e.g., LULC classes).
<code>sf_hex_grid</code>	An <code>sf</code> object containing polygonal geometries (e.g., H3 hexagons). Must contain a column named <code>h3_address</code> for joining and grouping.
<code>proportion</code>	Logical. If <code>TRUE</code> (default), the output values are the proportion of the polygon area covered by each category (summing to 1 for covered area). If <code>FALSE</code> , the output is the raw sum of the coverage fraction (area).

Details

The function uses a custom function with `exactextractr::exact_extract` to perform three critical steps:

1. **Filtering NA/NaN:** Raster cells with missing values (NA) are explicitly excluded from the calculation, preventing the creation of a `_prop_NaN` column.
2. **Area Consolidation:** It sums the coverage fractions for all fragments belonging to the same category within the same hexagon, which is essential when polygons have been clipped or fragmented.
3. **Numerical Ordering:** The final columns are explicitly sorted based on the numerical value of the category (e.g., `_prop_70` appears before `_prop_80`) to correct the default alphanumeric sorting behavior of `tidyr::pivot_wider`.

Value

An sf object identical to `sf_hex_grid`, but with new columns appended for each categorical value found in the raster. Column names follow the pattern `<layer_name>_prop_<category_value>`. Columns are **numerically ordered** by the category value.

Examples

```
library(sf)
library(terra)

# Create a simple categorical SpatRaster
lulc <- terra::rast(
  nrows = 20, ncols = 20,
  xmin = -85.0, xmax = -83.0,
  ymin = 9.0, ymax = 11.0,
  crs = "EPSG:4326"
)
terra::values(lulc) <- sample(1:4, terra::ncell(lulc), replace = TRUE)
names(lulc) <- "landuse"

# Define categorical levels explicitly
levels(lulc) <- data.frame(
  value = 1:4,
  class = c("forest", "grassland", "urban", "water")
)

# Create a simple hexagon grid as sf polygons (smaller than raster extent)
hex_grid <- sf::st_make_grid(
  sf::st_as_sfc(sf::st_bbox(c(
    xmin = -84.5, xmax = -83.5,
    ymin = 9.5, ymax = 10.5
  ))), crs = sf::st_crs(4326)),
  n = c(3, 3),
  square = FALSE
)
h7 <- sf::st_sf(h3_address = paste0("hex_", seq_along(hex_grid)),
  geometry = hex_grid)

# Extract categorical raster values by hexagon
lulc_p <- h3sdm_extract_cat(lulc, h7, proportion = TRUE)
head(lulc_p)
```

h3sdm_extract_num	<i>Extract Area-Weighted Mean from Numeric Raster Stack</i>
-------------------	-------------------------------------------------------------

Description

Calculates the **area-weighted mean** value for each layer in a numeric SpatRaster (or single layer) within each polygon feature of an sf object. This function is designed to efficiently summarize continuous environmental variables (such as bioclimatic data) for predefined spatial units (e.g., H3 hexagons). It utilizes `exactextractr` to ensure highly precise zonal statistics by accounting for sub-pixel coverage fractions.

Usage

```
h3sdm_extract_num(spat_raster_multi, sf_hex_grid)
```

Arguments

`spat_raster_multi` A SpatRaster object from the `terra` package. Must contain numeric layers (can be a single layer or a stack/brick).

`sf_hex_grid` An sf object containing polygonal geometries (e.g., H3 hexagons). Must be a valid set of polygons for extraction.

Details

The function relies on `exactextractr::exact_extract` with `fun = "weighted_mean"` and `weights = "area"`. This methodology is crucial for maintaining spatial accuracy when polygons are irregular or small relative to the raster resolution. A critical check (nrow match) is performed before binding columns to ensure data integrity and prevent misalignment errors.

Value

An sf object identical to `sf_hex_grid`, but with new columns appended. The new column names match the original SpatRaster layer names. The values represent the area-weighted mean for that variable within each polygon.

Examples

```
library(sf)
library(terra)

# Create a SpatRaster stack with two numeric layers (e.g., bioclimatic variables)
bio1 <- terra::rast(
  nrows = 10, ncols = 10,
  xmin = -84.5, xmax = -83.5,
  ymin = 9.5, ymax = 10.5,
```

```

    crs = "EPSG:4326"
  )
  bio2 <- bio1
  terra::values(bio1) <- runif(terra::ncell(bio1), 15, 30)
  terra::values(bio2) <- runif(terra::ncell(bio2), 500, 3000)
  names(bio1) <- "bio1_temp"
  names(bio2) <- "bio12_precip"
  bio <- c(bio1, bio2)

# Create a simple hexagon grid as sf polygons
hex_grid <- sf::st_make_grid(
  sf::st_as_sf(sf::st_bbox(c(
    xmin = -84.5, xmax = -83.5,
    ymin = 9.5, ymax = 10.5
  )), crs = sf::st_crs(4326)),
  n = c(3, 3),
  square = FALSE
)
h7 <- sf::st_sf(h3_address = paste0("hex_", seq_along(hex_grid)),
  geometry = hex_grid)

# Extract numeric raster values by hexagon (mean per cell)
bio_p <- h3sdm_extract_num(bio, h7)
head(bio_p)

```

h3sdm_fit_model

Fits an SDM workflow to data using resampling and prepares it for stacking.

Description

Fits a Species Distribution Model (SDM) workflow to resampling data (cross-validation). This function is the main training step and optionally configures the results to be used with the 'stacks' package. Supports both classification (presence/absence) and regression (count-based) models, detected automatically from the workflow mode.

Usage

```

h3sdm_fit_model(
  workflow,
  data_split,
  presence_data = NULL,
  truth_col = NULL,
  pred_col = NULL,
  for_stacking = FALSE,
  ...
)

```

Arguments

<code>workflow</code>	A 'workflow' object from tidymodels (e.g., GAM or Random Forest).
<code>data_split</code>	An 'rsplit' or 'rset' object (e.g., result of <code>vfold_cv</code> or <code>spatial_block_cv</code>).
<code>presence_data</code>	(Optional) Original presence data (used for extended metrics).
<code>truth_col</code>	Column name of the response variable. Defaults to "presence" for classification models and "count" for regression models.
<code>pred_col</code>	Column name for the prediction of the class of interest. Defaults to ".pred_1" for classification models and ".pred" for regression models.
<code>for_stacking</code>	Logical. If TRUE, uses <code>control_stack_resamples()</code> to save all workflow information required for the 'stacks' package. If FALSE, uses the standard control with <code>save_pred = TRUE</code> .
<code>...</code>	Arguments passed on to other functions (e.g., to <code>tune::fit_resamples</code> if needed).

Value

A list with three elements:

- `cv_model`: The result of `fit_resamples()`.
- `final_model`: The model fitted to the entire training set (first split).
- `metrics`: Extended evaluation metrics (if `presence_data` is provided).

`h3sdm_fit_models`

Fit and evaluate multiple H3SDM species distribution models

Description

Fits one or more species distribution models using tidymodels workflows and a specified resampling scheme, then computes standard metrics (ROC AUC, accuracy, sensitivity, specificity, F1-score, Kappa) along with TSS (True Skill Statistic) and the Boyce index for model evaluation. Returns both the fitted models and a comparative metrics table.

Usage

```
h3sdm_fit_models(
  workflows,
  data_split,
  presence_data = NULL,
  truth_col = "presence",
  pred_col = ".pred_1"
)
```

Arguments

<code>workflows</code>	A named list of tidymodels workflows created with <code>h3sdm_workflow()</code> or manually.
<code>data_split</code>	A resampling object (e.g., from <code>vfold_cv()</code> or <code>h3sdm_spatial_cv()</code>) for cross-validation.
<code>presence_data</code>	An sf object or tibble with presence locations to compute the Boyce index (optional).
<code>truth_col</code>	Character. Name of the column containing true presence/absence values (default "presence").
<code>pred_col</code>	Character. Name of the column containing predicted probabilities (default ".pred_1").

Value

A list with two elements:

models A list of fitted models returned by `h3sdm_fit_model()`.

metrics A tibble with one row per model per metric, including standard yardstick metrics, TSS, and Boyce index.

Examples

```
## Not run:
# Example requires prepared recipes and resampling objects
mod_log <- logistic_reg() %>%
  set_engine("glm") %>%
  set_mode("classification")

mod_rf <- rand_forest() %>%
  set_engine("ranger") %>%
  set_mode("classification")

workflows_list <- list(
  logistic = h3sdm_workflow(mod_log, my_recipe),
  rf       = h3sdm_workflow(mod_rf, my_recipe)
)

results <- h3sdm_fit_models(
  workflows      = workflows_list,
  data_split     = my_cv_folds,
  presence_data  = presence_sf
)
metrics_table <- results$metrics

## End(Not run)
```

h3sdm_get_grid	<i>Generar cuadrícula H3 para un área de interés</i>
----------------	------------------------------------------------------

Description

Crea una cuadrícula de hexágonos H3 que cubre un área de interés (`sf_object`), asegurando que las celdas se ajusten a la extensión del área y se recorten opcionalmente al contorno del AOI.

Esta función es equivalente a la usada en los módulos de paisaje de `h3sdm`, pero con el nombre estandarizado para mantener consistencia en el paquete.

Usage

```
h3sdm_get_grid(sf_object, res = 6, expand_factor = 0.1, clip_to_aoi = TRUE)
```

Arguments

<code>sf_object</code>	Objeto <code>sf</code> que define el área de interés (AOI).
<code>res</code>	Entero entre 1 y 16. Define la resolución del índice H3. Valores mayores producen hexágonos más pequeños.
<code>expand_factor</code>	Valor numérico que amplía ligeramente el bounding box del AOI antes de generar los hexágonos. Por defecto 0.1.
<code>clip_to_aoi</code>	Lógico (TRUE o FALSE), indica si los hexágonos deben recortarse exactamente al contorno del AOI. Por defecto TRUE.

Value

Un objeto `sf` con los hexágonos H3 correspondientes al área de interés, con geometrías válidas (MULTIPOLYGON).

Examples

```
## Not run:
library(sf)

# Crear un polígono de ejemplo
cr <- st_as_sf(data.frame(
  lon = c(-85, -85, -83, -83, -85),
  lat = c(9, 11, 11, 9, 9)
), coords = c("lon", "lat"), crs = 4326) |>
  summarise(geometry = st_combine(geometry)) |>
  st_cast("POLYGON")

# Generar cuadrícula H3
h5 <- h3sdm_get_grid(cr, res = 5)
plot(st_geometry(h5))

## End(Not run)
```

h3sdm_get_records	<i>Query Species Occurrence Records within an H3 Area of Interest (AOI)</i>
-------------------	-----------------------------------------------------------------------------

Description

Downloads species occurrence records from providers (e.g., GBIF, iNaturalist, BiodataCR) and filters them by the exact polygonal boundary of the Area of Interest (AOI). Providers supported by spocc (e.g., "gbif", "inat") are queried via `spocc::occ()`. "biodatacr" is queried via `rbiodatacr::bdcr_occurrences()` and its output is standardized to the same sf format.

Usage

```
h3sdm_get_records(
  species,
  aoi_sf,
  providers = NULL,
  limit = 500,
  remove_duplicates = FALSE,
  date = NULL
)
```

Arguments

species	Character string specifying the species name to query (e.g., "Puma concolor").
aoi_sf	An sf object defining the Area of Interest (AOI). Its CRS will be transformed to WGS84 (EPSG:4326) before query.
providers	Character vector of data providers to query. Accepted values: any provider supported by spocc (e.g., "gbif", "inat") plus "biodatacr" for BiodataCR (Costa Rica). If NULL (default), all spocc providers are used.
limit	Numeric. Maximum number of records to retrieve per provider. Default is 500.
remove_duplicates	Logical. If TRUE, records with identical coordinates are removed. Default is FALSE.
date	Character vector specifying a date range (e.g., <code>c('2000-01-01', '2020-12-31')</code>). Applied to spocc providers only.

Details

When "biodatacr" is included in providers, the function calls `rbiodatacr::bdcr_occurrences()` and standardizes its output (decimalLatitude/decimalLongitude) to the same sf geometry format used by the spocc providers. Records from all providers are then combined and clipped to the AOI.

Value

An sf object of points with the filtered occurrence records whose geometry falls strictly within the aoi_sf boundary. If no records are found, an empty sf object with the expected structure is returned.

Examples

```
library(sf)

aoi_sf <- sf::st_as_sf(
  data.frame(
    lon = c(-84.5, -83.5, -83.5, -84.5, -84.5),
    lat = c(9.5, 9.5, 10.5, 10.5, 9.5)
  ) |>
  {\(d) sf::st_sfc(sf::st_polygon(list(as.matrix(d))), crs = 4326)}(),
  data.frame(id = 1)
)

# GBIF only
records <- h3sdm_get_records(
  species = "Puma concolor",
  aoi_sf = aoi_sf,
  providers = "gbif",
  limit = 100
)

# GBIF + BiodataCR (Costa Rica)
records_cr <- h3sdm_get_records(
  species = "Agalychnis callidryas",
  aoi_sf = aoi_sf,
  providers = c("gbif", "biadatacr"),
  limit = 200
)
```

h3sdm_get_records_by_hexagon

Download Species Records and Count Occurrences per H3 Hexagon

Description

This function downloads occurrence records for one or more species and counts the number of records falling inside each H3 hexagon covering the specified Area of Interest (AOI).

Usage

```
h3sdm_get_records_by_hexagon(
  species,
  aoi_sf,
```

```

    res = 6,
    providers = NULL,
    remove_duplicates = FALSE,
    date = NULL,
    expand_factor = 0.1,
    limit = 500
  )

```

Arguments

<code>species</code>	Character vector of species names to query (e.g., <code>c("Puma concolor", "Panthera onca")</code>).
<code>aoi_sf</code>	An <code>sf</code> polygon defining the Area of Interest (AOI).
<code>res</code>	Numeric. H3 resolution level (default 6), determining hexagon size.
<code>providers</code>	Character vector of data providers (e.g., "gbif"). If NULL, all providers are used.
<code>remove_duplicates</code>	Logical. If TRUE, duplicate coordinates are removed before counting. Default is FALSE.
<code>date</code>	Character vector specifying a date range (e.g., <code>c('2000-01-01', '2020-12-31')</code>).
<code>expand_factor</code>	Numeric. Factor to expand the AOI bounding box before generating the H3 grid. Default is 0.1.
<code>limit</code>	Numeric. Maximum number of records to retrieve per species per provider. Default is 500.

Details

Download Species Records and Count Occurrences per H3 Hexagon

For each species:

1. An H3 grid is generated across the AOI using `h3sdm_get_grid()`.
2. Occurrence records are downloaded using `h3sdm_get_records()`.
3. Points are joined to the hexagonal grid with `sf::st_join()`.
4. Counts of points per hexagon are calculated.
5. Counts are merged into the main hex grid.

The function ensures column names derived from species names are safe in R by replacing spaces with underscores and handles API failures gracefully.

Value

An `sf` object containing the H3 hexagonal grid (MULTIPOLYGON) with additional integer columns for each species (spaces replaced by underscores) showing the count of occurrence records in each hexagon. Hexagons with no records have 0.

See Also

[h3sdm_get_grid](#), [h3sdm_get_records](#)

Examples

```

library(sf)

# Create a simple AOI polygon in Costa Rica
aoi_sf <- sf::st_as_sf(
  data.frame(id = 1),
  geometry = sf::st_sfc(
    sf::st_polygon(list(matrix(
      c(-84.5, 9.5,
        -83.5, 9.5,
        -83.5, 10.5,
        -84.5, 10.5,
        -84.5, 9.5),
      ncol = 2, byrow = TRUE
    ))),
    crs = 4326
  )
)

hex_counts <- h3sdm_get_records_by_hexagon(
  species = c("Agalychnis callidryas", "Smilisca baudinii"),
  aoi_sf = aoi_sf,
  res = 7,
  providers = "gbif",
  limit = 100
)

print(hex_counts)

```

h3sdm_pa

Generate presence/pseudo-absence dataset for a species

Description

Generates a hexagonal grid over the AOI, assigns species presence records to hexagons, and samples pseudo-absences from hexagons with no records.

Usage

```

h3sdm_pa(
  species,
  aoi_sf,
  res = 6,
  n_pseudoabs = 500,
  providers = NULL,
  remove_duplicates = FALSE,
  date = NULL,

```

```

    limit = 500,
    expand_factor = 0.1
  )

```

Arguments

species	character	Species name (single string) for which records are requested.
aoi_sf	sf	AOI (area of interest) polygon.
res	integer	H3 resolution for the hexagonal grid.
n_pseudoabs	integer	Number of pseudo-absence hexagons to sample.
providers	character	Optional vector of data providers. Accepted values: any provider supported by spocc (e.g., "gbif", "inat") plus "biodatacr" for BiodataCR (Costa Rica), queried via the rbiodatacr package. If NULL (default), all spocc providers are used.
remove_duplicates	logical	Remove duplicate records at the same coordinates.
date	character	Optional date filter for records.
limit	integer	Maximum number of records to download.
expand_factor	numeric	Factor to expand AOI before creating hex grid.

Value

sf object with columns:

- h3_address: H3 index of the hexagon.
- presence: factor with levels "0" (pseudo-absence) and "1" (presence).
- geometry: MULTIPOLYGON of each hexagon.

Examples

```

## Not run:
data(cr_outline_c, package = "h3sdm")
dataset <- h3sdm_pa("Agalychnis callidryas", cr_outline_c, res = 7, n_pseudoabs = 100)

## End(Not run)

```

h3sdm_pa_from_records Generate presence/pseudo-absence dataset from user-provided records

Description

Adapts a user-provided dataset with presence records (from personal fieldwork, BiodataCR, or any other source) into a hexagonal presence/pseudo-absence dataset ready for analysis with h3sdm. The input can be a data.frame with coordinate columns or an sf object. Coordinates are assumed to be in WGS84 (EPSG:4326).

Usage

```
h3sdm_pa_from_records(
  records,
  aoi_sf,
  res = 6,
  n_pseudoabs = 500,
  expand_factor = 0.1,
  lon_col = "lon",
  lat_col = "lat",
  species_col = NULL,
  geospatial_filter = TRUE
)
```

Arguments

<code>records</code>	data.frame or sf object containing presence records.
<code>aoi_sf</code>	sf AOI (area of interest) polygon.
<code>res</code>	integer H3 resolution for the hexagonal grid.
<code>n_pseudoabs</code>	integer Number of pseudo-absence hexagons to sample.
<code>expand_factor</code>	numeric Factor to expand AOI before creating hex grid.
<code>lon_col</code>	character Name of the longitude column. Ignored if records is already an sf object.
<code>lat_col</code>	character Name of the latitude column. Ignored if records is already an sf object.
<code>species_col</code>	character Optional. Name of the column containing the species name. If provided, the column is retained in the output as metadata.
<code>geospatial_filter</code>	logical If TRUE (default) and the input contains a <code>geospatialKosher</code> column, records with <code>geospatialKosher == FALSE</code> are removed before processing. Ignored if the column is absent.

Value

sf object with columns:

h3_address H3 index of the hexagon.

presence Factor with levels "0" (pseudo-absence) and "1" (presence).

species Species name (only if `species_col` is provided).

geometry MULTIPOLYGON of each hexagon.

Examples

```
data(cr_outline_c, package = "h3sdm")

my_records <- data.frame(
  lon = c(-84.1, -84.2, -83.9),
```

```
lat = c(9.9, 10.1, 9.8),
species = "Agalychnis callidryas"
)

dataset <- h3sdm_pa_from_records(
  records      = my_records,
  aoi_sf       = cr_outline_c,
  res          = 7,
  n_pseudoabs = 100,
  lon_col      = "lon",
  lat_col      = "lat",
  species_col  = "species"
)
```

h3sdm_predict*Predict species presence probability or counts using H3 hexagons*

Description

Uses a fitted tidymodels workflow (from `h3sdm_fit_model` or a standalone workflow) to predict species presence probabilities or counts on a new spatial H3 grid. Automatically generates centroid coordinates (x and y) if missing. The `new_data` must contain the same predictor variables as used in model training. Model mode (classification or regression) is detected automatically.

Usage

```
h3sdm_predict(fit_object, new_data)
```

Arguments

<code>fit_object</code>	A fitted tidymodels workflow or the output list from <code>h3sdm_fit_model</code> .
<code>new_data</code>	An sf object containing the spatial grid and the same predictor variables used for model training.

Value

An sf object with the original geometry and a new column prediction containing the predicted probability of presence (classification) or predicted count (regression) for each hexagon.

See Also

[h3sdm_fit_model\(\)](#), [h3sdm_aoa\(\)](#)

Examples

```
## Not run:
# Predict presence probabilities on a new hex grid
predictions_sf <- h3sdm_predict(
  fit_object = fitted_model,
  new_data   = grid_sf
)

## End(Not run)
```

h3sdm_predictors

Combine Predictor Data from Multiple sf Objects

Description

This function merges predictor variables from multiple `sf` objects into a single `sf` object. It preserves the geometry from the first input and joins columns from the other `sf` objects using a common key (`h3_address` or `ID`).

Usage

```
h3sdm_predictors(...)
```

Arguments

... Two or more `sf` objects containing predictor variables. The first object must contain the geometry to preserve. All objects must share a common key column (`h3_address` or `ID`).

Details

The function uses a left join based on the `h3_address` column if present, otherwise it falls back to `ID`. Geometries from the right-hand side `sf` objects are dropped to avoid conflicts, and the final geometry is cast to `MULTIPOLYGON`.

Value

An `sf` object containing the geometry of the first input and all predictor columns from all provided `sf` objects.

Examples

```
## Not run:
# Combine sf objects with different predictor types into one
combined <- h3sdm_predictors(num_sf, cat_sf, it_sf)
head(combined)

## End(Not run)
```

`h3sdm_recipe`*Create a tidymodels recipe for H3-based SDMs*

Description

Prepares an `sf` object with H3 hexagonal data for modeling with the `tidymodels` ecosystem. Extracts centroid coordinates, assigns appropriate roles to the variables automatically, and returns a ready-to-use recipe for modeling species distributions.

Usage

```
h3sdm_recipe(data, response_col = "presence")
```

Arguments

<code>data</code>	An <code>sf</code> object, typically the output of <code>h3sdm_data()</code> , including species presence-absence or count data, H3 addresses, and environmental predictors. The geometry must be of type MULTIPOLYGON.
<code>response_col</code>	character Name of the column to use as the outcome (response variable). Default "presence" for presence/absence models. Use "count" when working with count data generated by <code>h3sdm_count_from_records()</code> .

Details

This function prepares spatial H3 grid data for species distribution modeling:

- Extracts centroid coordinates (x and y) from MULTIPOLYGON geometries.
- Removes the geometry column to create a purely tabular dataset for `tidymodels`.
- Assigns roles to columns:
 - `response_col` → "outcome" (target variable)
 - `h3_address` → "id" (used for joining predictions later)
 - x and y → "spatial_predictor"
- All other columns are assigned "predictor" role.

Value

A `tidymodels` recipe object (class "h3sdm_recipe") ready for modeling.

Examples

```
## Not run:  
# Presence/absence model (default)  
sdm_recipe <- h3sdm_recipe(combined_data)  
  
# Count-based model  
sdm_recipe <- h3sdm_recipe(combined_data, response_col = "count")
```

```
## End(Not run)
```

h3sdm_recipe_gam	<i>Creates a 'recipe' object for Generalized Additive Models (GAM) in SDM</i>
------------------	-------------------------------------------------------------------------------

Description

This function prepares an `sf` object for use in a Species Distribution Model (SDM) workflow with the 'mgcv' GAM engine within the 'tidymodels' ecosystem. Extracts centroid coordinates and assigns appropriate roles to all variables, including the response variable and spatial coordinates.

Usage

```
h3sdm_recipe_gam(data, response_col = "presence")
```

Arguments

data	An <code>sf</code> object containing the response variable, environmental predictors, and geometry (e.g., H3 hexagon polygons).
response_col	character Name of the column to use as the outcome (response variable). Default "presence" for presence/absence models. Use "count" when working with count data generated by <code>h3sdm_count_from_records()</code> .

Details

Assigned Roles:

- outcome: the column specified in `response_col`.
- id: "h3_address" (cell identifier, not used for modeling).
- predictor: all other variables, including `x` and `y` for the GAM spatial smooth term ($s(x, y, bs = "tp")$).

Value

A recipe object of class `h3sdm_recipe_gam`, ready to be chained with additional preprocessing steps.

See Also

Other `h3sdm_tools`: [h3sdm_stack_fit\(\)](#), [h3sdm_workflow_gam\(\)](#)

Examples

```

library(sf)
library(recipes)

set.seed(42)
n <- 20

pts <- sf::st_as_sf(
  data.frame(
    h3_address = paste0("hex_", seq_len(n)),
    presence   = sample(0:1, n, replace = TRUE),
    count      = sample(0:9, n, replace = TRUE),
    bio1_temp  = runif(n, 15, 30),
    bio12_precip = runif(n, 500, 3000)
  ),
  geometry = sf::st_sfc(
    lapply(seq_len(n), function(i) {
      sf::st_point(c(runif(1, -84.5, -83.5), runif(1, 9.5, 10.5)))
    })
  ),
  crs = 4326
)

# Presence/absence model (default)
gam_rec <- h3sdm_recipe_gam(pts)

# Count-based model
gam_rec <- h3sdm_recipe_gam(pts, response_col = "count")

```

h3sdm_spatial_cv

Create a spatial-aware cross-validation split for H3 data

Description

Generates a spatially aware cross-validation split for species distribution modeling using H3 hexagonal grids. This helps avoid inflated model performance estimates caused by spatial autocorrelation, producing more robust model evaluation.

Usage

```
h3sdm_spatial_cv(data, method = "block", v = 5, ...)
```

Arguments

data	An sf object, typically the output of h3sdm_data().
method	Character. The spatial resampling method to use:

"block" Use `spatialsample::spatial_block_cv()` for block-based spatial CV.

"cluster" Use `spatialsample::spatial_clustering_cv()` for cluster-based spatial CV.

`v` Integer. Number of folds (default = 5).

`...` Additional arguments passed to the underlying `spatialsample` function.

Details

Spatial cross-validation avoids overly optimistic performance estimates by ensuring that training and testing data are spatially separated.

- **"block"**: Divides the spatial domain into contiguous blocks.
- **"cluster"**: Groups locations into spatial clusters before splitting.

Value

An `rsplit` object (from `rsample`) representing the spatial CV folds.

Examples

```
## Not run:
# Example: Create spatial cross-validation splits for H3 data

# Block spatial CV with default folds
spatial_cv_block <- h3sdm_spatial_cv(combined_data, method = "block")

# Cluster spatial CV with 10 folds
spatial_cv_cluster <- h3sdm_spatial_cv(combined_data, method = "cluster", v = 10)

## End(Not run)
```

`h3sdm_stack_fit` *Creates and fully fits an ensemble model (Stack).*

Description

This function combines the process of creating the model stack, optimizing the weights (`blend_predictions`), and fitting the base models to the complete training set (`fit_members()`) into a single step.

Warning: It does not follow the canonical `tidymodels` flow but is convenient. It requires that the fitting results were generated using `h3sdm_fit_model(..., for_stacking = TRUE)`.

Usage

```
h3sdm_stack_fit(..., non_negative = TRUE, metric = NULL)
```

Arguments

...	List objects that are the result of <code>h3sdm_fit_model()</code> . Each object must contain the <code>cv_model</code> element (result of <code>fit_resamples</code>).
<code>non_negative</code>	Logical. If TRUE (default), forces the candidate model weights to be non-negative.
<code>metric</code>	The metric used to optimize the combination of weights.

Value

A list containing two elements: `blended_model` (the stack after blending) and `final_model` (a fully fitted `model_stack` object). The `final_model` is ready for direct prediction with `predict()`.

See Also

Other h3sdm_tools: [h3sdm_recipe_gam\(\)](#), [h3sdm_workflow_gam\(\)](#)

<code>h3sdm_workflow</code>	<i>Create a tidymodels workflow for H3-based SDMs</i>
-----------------------------	-------------------------------------------------------

Description

Combines a model specification and a prepared recipe into a single tidymodels workflow. This workflow is suitable for species distribution modeling using H3 hexagonal grids and can be directly fitted or cross-validated.

Usage

```
h3sdm_workflow(model_spec, recipe)
```

Arguments

<code>model_spec</code>	A tidymodels model specification (e.g., <code>logistic_reg()</code> , <code>rand_forest()</code> , or <code>boost_tree()</code>), describing the model type and engine to use for fitting. Use <code>set_mode("classification")</code> for presence/absence models and <code>set_mode("regression")</code> for count-based models (species richness, detections, or individuals).
<code>recipe</code>	A tidymodels recipe object, typically created with <code>h3sdm_recipe()</code> , which preprocesses the data and defines predictor/response roles. Use <code>response_col = "count"</code> in <code>h3sdm_recipe()</code> when working with count data.

Details

The function creates a workflow that combines preprocessing and modeling steps. This encapsulation allows consistent model training and evaluation with tidymodels functions like `fit()` or `fit_resamples()`, and is particularly useful when applying multiple models in parallel.

Choosing the model mode:

- For **presence/absence** data: use `set_mode("classification")`.
- For **count** data (species richness, detections, individuals): use `set_mode("regression")`.

Value

A workflow object ready to be used for model fitting with `fit()` or cross-validation.

Examples

```
## Not run:
library(parsnip)

# --- Presence/absence model ---
rf_spec_pa <- rand_forest() %>%
  set_engine("ranger") %>%
  set_mode("classification")

rec_pa <- h3sdm_recipe(combined_data)

wf_pa <- h3sdm_workflow(model_spec = rf_spec_pa, recipe = rec_pa)

# --- Count-based model ---
rf_spec_count <- rand_forest() %>%
  set_engine("ranger") %>%
  set_mode("regression")

rec_count <- h3sdm_recipe(combined_data, response_col = "count")

wf_count <- h3sdm_workflow(model_spec = rf_spec_count, recipe = rec_count)

## End(Not run)
```

h3sdm_workflows

Create multiple tidymodels workflows for H3-based SDMs

Description

Creates a list of tidymodels workflows from multiple model specifications and a prepared recipe. This is useful for comparing different modeling approaches in species distribution modeling using H3 hexagonal grids.

Usage

```
h3sdm_workflows(model_specs, recipe)
```

Arguments

`model_specs` A named list of tidymodels model specifications (e.g., `logistic_reg()`, `rand_forest()`, `boost_tree()`), where each element specifies a different modeling approach. All specifications must use the same mode: `set_mode("classification")` for presence/absence models or `set_mode("regression")` for count-based models.

`recipe` A tidymodels recipe object, typically created with `h3sdm_recipe()`, which prepares and preprocesses the data for modeling. Use `response_col = "count"` in `h3sdm_recipe()` when working with count data.

Details

This function automates the creation of workflows for multiple model specifications. Each workflow combines the same preprocessing steps (`recipe`) with a different modeling method, facilitating systematic comparison of models.

Choosing the model mode:

- For **presence/absence** data: use `set_mode("classification")` for all model specifications.
- For **count** data (species richness, detections, individuals): use `set_mode("regression")` for all model specifications.

Value

A named list of workflow objects, one per model specification.

Examples

```
## Not run:
library(parsnip)

# --- Presence/absence models ---
specs_pa <- list(
  rf = rand_forest() %>% set_engine("ranger") %>% set_mode("classification"),
  glm = logistic_reg() %>% set_engine("glm") %>% set_mode("classification")
)

rec_pa <- h3sdm_recipe(combined_data)

wfs_pa <- h3sdm_workflows(model_specs = specs_pa, recipe = rec_pa)

# --- Count-based models ---
specs_count <- list(
  rf = rand_forest() %>% set_engine("ranger") %>% set_mode("regression"),
  xgb = boost_tree() %>% set_engine("xgboost") %>% set_mode("regression")
)

rec_count <- h3sdm_recipe(combined_data, response_col = "count")

wfs_count <- h3sdm_workflows(model_specs = specs_count, recipe = rec_count)

## End(Not run)
```

h3sdm_workflow_gam	<i>Creates a tidymodels workflow for Generalized Additive Models (GAM).</i>
--------------------	-----------------------------------------------------------------------------

Description

This function constructs a workflow object by combining a GAM model specification (`gen_additive_mod` with the `mgcv` engine) with either a recipe object or an explicit model formula.

It is optimized for Species Distribution Models (SDM) that use smooth splines, ensuring that the specialized GAM formula (containing `s()` terms) is correctly passed to the model, even when a recipe is provided for general data preprocessing.

Usage

```
h3sdm_workflow_gam(gam_spec, recipe = NULL, formula = NULL)
```

Arguments

<code>gam_spec</code>	A parsnip model specification of type <code>gen_additive_mod()</code> , configured with <code>set_engine("mgcv")</code> . Use <code>set_mode("classification")</code> for presence/absence models and <code>set_mode("regression")</code> for count-based models.
<code>recipe</code>	(Optional) A recipes package recipe object (e.g., the output of <code>h3sdm_recipe_gam</code>). Used for general data preprocessing like normalization or dummy variable creation.
<code>formula</code>	(Optional) A formula object that defines the structure of the GAM, including smooth terms (e.g., $y \sim s(x_1) + s(x, y)$). If provided alongside <code>recipe</code> , this formula overrides the recipe's implicit formula for the final model fit.

Details

Formula Priority:

- If **only** `recipe` is provided, the workflow uses the recipe's implicit formula (e.g., `outcome ~ .`).
- If `recipe` **and** `formula` are provided, the workflow uses the recipe for data preprocessing but explicitly passes the formula to the `mgcv` engine for fitting, enabling the use of specialized terms like `s(x, y)`.

Choosing the model mode and family:

- For **presence/absence** data: use `set_mode("classification")`. The `mgcv` engine uses `binomial()` family by default.
- For **count** data (species richness, detections, individuals): use `set_mode("regression")` and specify `set_engine("mgcv", family = poisson())`.

Value

A workflow object, ready for fitting with `fit()` or resampling with `fit_resamples()` or `tune_grid()`.

See Also

Other h3sdm_tools: [h3sdm_recipe_gam\(\)](#), [h3sdm_stack_fit\(\)](#)

Examples

```
## Not run:
library(parsnip)

# --- Presence/absence model (binomial) ---
gam_spec_pa <- gen_additive_mod() %>%
  set_engine("mgcv") %>%
  set_mode("classification")

gam_formula_pa <- presence ~ s(bio1) + s(bio12) + s(x, y, bs = "tp")

base_rec_pa <- h3sdm_recipe_gam(data)

h3sdm_wf_pa <- h3sdm_workflow_gam(
  gam_spec = gam_spec_pa,
  recipe   = base_rec_pa,
  formula  = gam_formula_pa
)

# --- Count-based model (Poisson) ---
gam_spec_count <- gen_additive_mod() %>%
  set_engine("mgcv", family = poisson()) %>%
  set_mode("regression")

gam_formula_count <- count ~ s(bio1) + s(bio12) + s(x, y, bs = "tp")

base_rec_count <- h3sdm_recipe_gam(data, response_col = "count")

h3sdm_wf_count <- h3sdm_workflow_gam(
  gam_spec = gam_spec_count,
  recipe   = base_rec_count,
  formula  = gam_formula_count
)

## End(Not run)
```

 records

Presence/pseudo-absence records for Silverstoneia flotator

Description

A dataset containing presence and pseudo-absence records for the species *Silverstoneia flotator* in Costa Rica, generated using H3 hexagonal grids at resolution 7.

Usage

records

Format

An sf object with columns:

h3_address H3 index of the hexagon

presence factor with levels "0" (pseudo-absence) and "1" (presence)

geometry MULTIPOLYGON of each hexagon

Source

Generated using `h3sdm_pa()` with occurrence data from GBIF (<https://www.gbif.org>).

Examples

```
data(records)
head(records)
table(records$presence)
```

Index

* datasets

cr_outline_c, 4
records, 37

* h3sdm_tools

h3sdm_recipe_gam, 30
h3sdm_stack_fit, 32
h3sdm_workflow_gam, 36

bioclim_current, 2
bioclim_future, 3

cr_outline_c, 4

h3sdm_aoa, 4
h3sdm_aoa(), 27
h3sdm_calculate_it_metrics, 6
h3sdm_classify, 7
h3sdm_compare_models, 8
h3sdm_count_from_records, 9
h3sdm_data, 11
h3sdm_data(), 4, 5
h3sdm_eval_metrics, 12
h3sdm_explain, 13
h3sdm_extract_cat, 14
h3sdm_extract_num, 16
h3sdm_fit_model, 17
h3sdm_fit_model(), 4, 5, 27
h3sdm_fit_models, 18
h3sdm_get_grid, 20, 23
h3sdm_get_records, 21, 23
h3sdm_get_records_by_hexagon, 22
h3sdm_pa, 24
h3sdm_pa_from_records, 25
h3sdm_predict, 27
h3sdm_predict(), 4, 5, 7
h3sdm_predictors, 28
h3sdm_recipe, 29
h3sdm_recipe_gam, 30, 36
h3sdm_recipe_gam(), 33, 37
h3sdm_spatial_cv, 31

h3sdm_spatial_cv(), 5
h3sdm_stack_fit, 32
h3sdm_stack_fit(), 30, 37
h3sdm_workflow, 33
h3sdm_workflow_gam, 36
h3sdm_workflow_gam(), 30, 33
h3sdm_workflows, 34

records, 37